



IMO MARINE UNDERLAY

"A hardwearing underlay, designed for the toughest marine and contract locations"

TECHNICAL SPECIFICATION & TYPICAL VALUES

- Conforms To IMO Flammability Resolution A653 (16) & MSC 61 (67)
- Complies with Marine Equipment Directive 96/98/EC
- Classified to BS 5808 : 1991 (2005) British Standard for Underlay
- Thermal Resistance : 1.77 Tog & Decibel Reduction Delta Lw : 33 dB
- Doublestick Castor Wheel Chair Test : 25000 + Revolutions

TYPICAL VALUES

Roll Length:	11m min
Roll Width:	137 cms +/- 1%
Roll Size:	15m2 +/- 1%
Density:	180 kg/m3 +/- 5%
Roll Weight:	17 kg +/- 5%
Thickness:	6mm +/- 5%

WHY CHOOSE GB UNDERLAY FOR YOUR BOAT?



- Conforms to the International Maritime Organisation's standards (IMO)
- Designed for marine use in stretch fit and double stick installations
- Protects carpets from premature wear
- Guaranteed for the lifetime of the carpet
- Excellent heat and sound insulation
- Recycled product and fully recyclable
- High Flame Retardency Properties
- An environmentally responsible product made in the UK
- Exclusively available to GB Foam for marine application.
- High density low weight product – advantages in weight and fuel saving

